

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	217,00
	R 1/4	521010	189,00
	R 3/8	521020	128,00
	R 1/2	521030	133,00
	R 3/4	521040	139,00
	R 1	521050	145,00
	R 1 1/4	521060	151,00
	R 1 1/2	521070	177,00
	R 2	521080	189,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	261,00
	R 1/4 LH	521110	227,00
	R 3/8 LH	521120	154,00
	R 1/2 LH	521130	160,00
	R 3/4 LH	521140	167,00
	R 1 LH	521150	174,00
	R 1 1/4 LH	521160	182,00
	R 1 1/2 LH	521170	213,00
	R 2 LH	521180	227,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	217,00
	NPT 1/4	521210	189,00
	NPT 3/8	521220	128,00
	NPT 1/2	521230	133,00
	NPT 3/4	521240	139,00
	NPT 1	521250	145,00
	NPT 1 1/4	521260	151,00
	NPT 1 1/2	521270	177,00
	NPT 2	521280	189,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	167,00
	M 20 x 1.5	521310	167,00
	M 25 x 1.5	521320	174,00
	M 32 x 1.5	521330	182,00
	M 40 x 1.5	521340	213,00
	M 50 x 1.5	521350	227,00



Right-hand
pipe thread



Left-hand
pipe thread



Info

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	98,50
	R 1/4	521012RWS	93,00
	R 3/8	521022RWS	93,00
	R 1/2	521032RWS	93,00
	R 3/4	521042RWS	101,80
	R 1	521052RWS	101,80
	R 1 1/4	521062RWS	101,80
	R 1 1/2	521072RWS	101,80
	R 2	521082RWS	101,80
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	119,00
	R 1/4 LH	521112RWS	112,00
	R 3/8 LH	521122RWS	112,00
	R 1/2 LH	521132RWS	112,00
	R 3/4 LH	521142RWS	123,00
	R 1 LH	521152RWS	123,00
	R 1 1/4 LH	521162RWS	123,00
	R 1 1/2 LH	521172RWS	123,00
	R 2 LH	521182RWS	122,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	98,50
	NPT 1/4	521212RWS	93,00
	NPT 3/8	521222RWS	93,00
	NPT 1/2	521232RWS	93,00
	NPT 3/4	521242RWS	101,80
	NPT 1	521252RWS	101,80
	NPT 1 1/4	521262RWS	101,80
	NPT 1 1/2	521272RWS	101,80
	NPT 2	521282RWS	101,80
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	123,00
	M 20 x 1.5	521312RWS	123,00
	M 25 x 1.5	521322RWS	123,00
	M 32 x 1.5	521332RWS	123,00
	M 40 x 1.5	521342RWS	123,00
	M 50 x 1.5	521352RWS	123,00



German Quality Product



Info