

# REMS Akku-Press ACC

Cordless radial press with automatic circuit control

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. For battery and corded operation.

Pipe pressing joints  $\varnothing$  10–108 (110) mm /  $\varnothing$   $\frac{3}{8}$ –4

Complete range of REMS pressing tongs/pressing rings for all common pressfitting systems, see page 156–176.

**REMS Akku-Press ACC – universal up to  $\varnothing$  110 mm. With automatic circuit control.**

**Secure crimping in seconds. Automatic locking of pressing tongs.**

### System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses (except for REMS Mini-Press ACC, REMS Mini-Press 22 V ACC) and radial presses of other makes.

All pressing tongs marked by a \* have another connection (**Patent DE 101 01 440, Patent EP 1 223 008, Patent US 6,739,172**) and also fit the manual radial press REMS Eco-Press. Thus simple, inexpensive stocking.

### Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 156–176). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect systemconformity, safe press jointing.

### Design

Compact, handy, light. Drive unit with battery only 4.3 kg. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. Integrated LED work light for illuminating the work place. Swivelling pressing tongs seat. Secure seating of pressing tongs/adaptor tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings.

### Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

### Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

### Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 3.0 Ah capacity, for long service life. Powerful and light. Li-Ion 14.4 V, 3.0 Ah battery for approx. 270 pressings Viega Profipress DN 15 per battery charge. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger for short charging times. Li-Ion 230 V/14.4 V voltage supply for mains operation 230 V instead of Li-Ion battery 14.4 V, as accessory.



Tested by electrosuisse >>>

German Quality Product



Info

### Supply format

**REMS Akku-Press ACC Basic-Pack.** Cordless radial press with automatic circuit control for producing pipe pressing joints  $\varnothing$  10–108 (110) mm,  $\varnothing$   $\frac{3}{8}$ –4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Integrated LED work light. Battery Li-Ion 14.4 V, 3.0 Ah, rapid charger Li-Ion/Ni-Cd 230 V or 110 V, 50–60 Hz, 65 W. In sturdy steel case.

Art.-No.
571014R220G

Other voltages on request.

### Accessories

Description	Art.-No.
<b>REMS pressing tongs/pressing rings</b> see page 156–176.	
<b>REMS cropping tongs</b> for threaded rods see page 179.	
<b>REMS cable shear</b> for electric cable see page 179.	
<b>REMS Akku-Press ACC drive unit</b> , without battery	571004R14
<b>Battery Li-Ion 14.4 V, 3.0 Ah</b>	571555R14
<b>Rapid charger Li-Ion/Ni-Cd 230 V</b> , 50–60 Hz, 65 W	571560R220G
<b>Voltage supply Li-Ion 230 V/14.4 V</b> for mains operation 230 V instead of battery Li-Ion 14.4 V.	571565R220
<b>Steel case</b> with inlay	571290R
<b>REMS cordless LED lamp</b> see page 97	175200R

