

# REMS expander heads P REMS expander heads P-CEF

Accessories for REMS pipe expander  
and other makes

## REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 227), REMS Akku-Ex-Press P 22V ACC cordless pipe expander (page 228–229) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.
<b>aquatherm grey pipe PB/PE-RT-Rohre</b>	AT P 14 × 2.0	150828
	AT P 16 × 2.0	150842
	AT P 18 × 2.0	150873
	AT P 20 × 2.0	150882
	AT P 25 × 2.3	150912
<b>aquatherm grey pipe Mehrschicht- Metallverbundrohre (MVR)</b>	AT V 16 × 2.4	150843
	AT V 20 × 2.4	150883
	AT V 25 × 2.7	150913
	AT V 32 × 3.2	150957
	AT V 40 × 3.5	150958
<b>General Fittings Serie 3400 PEX Gold-Fix</b>	RH HIS 16 × 2.2	150849
	RH HIS 20 × 2.8	150888
	RH HIS 25 × 3.5	150916
	RH HIS 32 × 4.4	150945
<b>General Fittings Serie 3400 PEX/AL/PEX Gold-Fix</b>	RH MKV 16.2 × 2.6	150858
	RH MKV 20 × 2.9	150897
	RH MKV 25 × 3.7	150926
	RH MKV 32 × 4.7	150952
<b>General Fittings Serie 3700 PEX</b>	TC 16	150855
	TC 18/20	150894
	TC 25	150923
	TC 32	150950
<b>General Fittings Serie 3700 PEX/AL/PEX</b>	TC 16	150855
	TC 18/20	150894
	TC 25	150923
	TC 32	150950
<b>HERZ QUICK FIX</b>	HC P 16 × 2.0	150806
	HC P 20 × 2.0	150807
	HC P 26 × 3.0	150808
	HC P 32 × 3.0	150809
<b>IVT PRINETO</b>	IV 16 × 2.2/17 × 2.8	150845
	IV 20 × 2.8/21 × 3.4	150885
	IV 25 × 3.5/26 × 4.0	150914
	IV 32 × 4.4/33 × 4.9	150943
<b>ÖAG COMDURO</b>	HC P 16 × 2.0	150806
	HC P 20 × 2.0	150807
	HC P 26 × 3.0	150808
	HC P 32 × 3.0	150809
<b>REHAU RAUTHERM (série S 5)</b>	RH 12 × 1.1	150812
	RH 16 × 1.5	150846
	RH 20 × 1.9	150886
	RH 25 × 2.3 (RH HAS 25 × 2.3)	150915
	RH 32 × 2.9 (RH HAS 32 × 2.9)	150944
<b>REHAU RAUTHERM S (REHAU HAS)</b>	RH HAS 17 × 2.0	150868
	RH HAS 20 × 2.0	150887
	RH HAS 25 × 2.3	150915
	RH HAS 32 × 2.9	150944
<b>REHAU RAUTITAN flex/ RAUTITAN gas flex/ RAUTITAN pink/ RAUTITAN his</b>	RH HIS 16 × 2.2	150849
	RH HIS 20 × 2.8	150888
	RH HIS 25 × 3.5	150916
	RH HIS 32 × 4.4	150945
	RH HIS 40 × 5.5	150946
<b>REHAU RAUTITAN stabil/ RAUTITAN gas stabil</b>	RH MKV 16.2 × 2.6	150858
	RH MKV 20 × 2.9	150897
	RH MKV 25 × 3.7	150926
	RH MKV 32 × 4.7	150952
	RH MKV 40 × 6.0	150947
<b>REHAU (GBR) EVERLOC</b>	RH 16 × 1.5	150846
	RH 20 × 1.9	150886
	RH 25 × 2.3 (RH HAS 25 × 2.3)	150915
	RH 32 × 2.9 (RH HAS 32 × 2.9)	150944
<b>REVEL</b>	RH HIS 16 × 2.2	150849
	RH HIS 20 × 2.8	150888
	RH HIS 25 × 3.5	150916
	RH HIS 32 × 4.4	150945
<b>Seppelfricke SD Sistemi Italia Neroflex</b>	RH HIS 16 × 2.2	150849
	RH HIS 20 × 2.8	150888
	RH HIS 25 × 3.5	150916
	RH HIS 32 × 4.4	150945
<b>Seppelfricke SD Sistemi Italia Sylver</b>	RH MKV 16.2 × 2.6	150858
	RH MKV 20 × 2.9	150897
	RH MKV 25 × 3.7	150926
	RH MKV 32 × 4.7	150952

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.

## Choose expander heads yourself!

Search for the required compression sleeve system in the table below and select the correct expander heads.



German Quality Product

## REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 227), REMS Akku-Ex-Press P 22V ACC cordless pipe expander (page 228–229) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.
<b>TECE TECEflex</b>	TC 12/14	150826
	TC 16	150855
	TC 18/20	150894
	TC 25	150923
	TC 32	150950
<b>TIEMME Assialpex</b>	IV 16 × 2.2/17 × 2.8	150845
	IV 20 × 2.8/21 × 3.4	150885
	IV 25 × 3.5/26 × 4.0	150914
	IV 32 × 4.4/33 × 4.9	150943
<b>Würth PRINETO</b>	IV 16 × 2.2/17 × 2.8	150845
	IV 20 × 2.8/21 × 3.4	150885
	IV 25 × 3.5/26 × 4.0	150914
	IV 32 × 4.4/33 × 4.9	150943

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.



## REMS expander heads P-CEF

Full range of REMS P-CEF expander heads for easy expanding of pipes/rings. Quick-change, without tools. The REMS P-CEF expander heads are system-specific and correspond to the requirements of the respective systems. Therefore, perfectly system-conformant, exact expanding. Conical angle 20°. Driven by REMS Akku-Ex-Press P-CEF 22V ACC cordless pipe expander (page 228–229), REMS Power-Ex-Press P-CEF ACC electro-hydraulic pipe expander (page 230) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P-CEF Ø × s	Art.-No.
<b>Brass &amp; Fittings PRESSMAN EasyFit</b>	P-CEF 16 × 1.8	150960
	P-CEF 20 × 1.9	150961
	P-CEF 25 × 2.3	150962
	P-CEF 32 × 2.9	150963
<b>Uponor Quick &amp; Easy</b>	P-CEF 16 × 1.8	150960
	P-CEF 20 × 1.9	150961
	P-CEF 25 × 2.3	150962
	P-CEF 32 × 2.9	150963
	P-CEF 40 × 3.7	150968
<b>Expander drive P-CEF (taper angle 20°), for holding the P-CEF expander heads 16–40 mm, 1/2–1 1/2"</b>		150515

System-related and/or national differences of the wall thickness s of the pipes must be considered in the selection of the expander heads.