

Universal, manual radial press for producing pipe pressing joints for all common pressfitting systems.

Pressing joints with plastic and multi-layer composite tubes  $\varnothing$  10–26 mm  
 $\varnothing$   $\frac{3}{8}$ –1"

Complete range of REMS pressing tongs for all common pressfitting systems, see page 156–176.

### REMS Eco-Press – universal up to $\varnothing$ 26 mm. Secure crimping in seconds.

#### System advantage

Only **one** type of pressing tongs for all REMS radial presses (except for REMS Mini-Press ACC, REMS Mini-Press 22 V ACC) and radial presses of other makes.

All pressing tongs marked by a \* have another connection (**Patent DE 101 01 440**, **Patent EP 1 223 008**, **Patent US 6,739,172**) and also fit the manual radial press REMS Eco-Press. Thus simple, inexpensive stocking.

#### Pressing tongs for all common systems

Complete assortment of REMS pressing tongs for all common pressfitting systems (page 156–176). Highly durable pressing tongs made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs are system-specific and correspond to the respective pressfitting system. Thus perfect systemconformity, safe press jointing.

#### Design

Compact, handy, light. Drive unit with short tubular arms only 1.6 kg. Works anywhere, free-hand, overhead, in confined areas. Secure seating of pressing tongs through locking pins. Dividable tubular arms for individual adjustment of leverage to accommodate different force demands of different pressfitting systems.

#### Pressing operation

A perfect joint is achieved when pressing tongs close completely. Final-lock-positioning, the pressing jaws remain in a closed position until opening. This way, the perfect pressing joint (completely closed pressing jaws) can be observed.



German Quality Product



Info

### Supply format

**REMS Eco-Press drive unit.** Manual radial press with final-lock-positioning for producing pressing joints of plastic and multi-layer composite tubes  $\varnothing$  10–26 mm,  $\varnothing$   $\frac{3}{8}$ –1". For operating with REMS pressing tongs. With dividable tubular arms. In skin package.

	Art.-No.
	574000R



### Accessories

Description	Art.-No.
<b>REMS pressing tongs</b> , see page 156–176.	
<b>REMS cropping tongs</b> for threaded rods see page 179.	
<b>Carrying bag</b> for drive unit and for 3 pressing tongs	574436R
<b>Steel case</b> with insert for drive unit and for 3 pressing tongs	574430R

