

# REMS Hurrican

Electric tube extractor

Powerful, compact electric tool for efficient machining of T-branches of hard and soft tubes for tube installations without fittings.

Hard and soft copper tubes  $\varnothing$  10–22 mm  
 $\varnothing$   $\frac{3}{8}$ – $\frac{7}{8}$ "  
 $s \leq 1.5$  mm

**REMS Hurrican – for making T-branches yourself. Inexpensive. Also on tubes already installed.**

### System advantage

Only one type of extractor tools for REMS Hurrican H, REMS Hurrican and REMS Twist/Hurrican. Simple, inexpensive storage. No confusion possible.

### Cost advantage

No costs for T-branches, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints.

### Design

Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head provides precise drilling without punching with any standard power drill. Drill depth-stop according to the size of T-branch. Tool holder for holding the extractor tools. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy grip wrench for clamping the tool holder onto the pipe.

### Drive

Proven drive unit with hexagon mount. Enormously powerful. Handy, light, only 1,5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

### Extractor tools

Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

### REMS Twist/Hurrican

Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage! See page 199.



German Quality Product



### Supply format

**REMS Hurrican Set.** Electric tube extractor for hard and soft copper tube  $\varnothing$  10–22 mm,  $\varnothing$   $\frac{3}{8}$ – $\frac{7}{8}$ " ,  $s \leq .5$  mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50–60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch). Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.
<b>Set 12-15-18-22</b>	151000R220
<b>Set 12-14-16-18-22</b>	151010R220
<b>Set <math>\frac{3}{8}</math>-<math>\frac{1}{2}</math>-<math>\frac{5}{8}</math>-<math>\frac{3}{4}</math>-<math>\frac{7}{8}</math>"</b>	151002R220

Other voltages on request.



### Accessories

Description	Tubes $\varnothing$ mm/inch	Art.-No.
<b>Extractor tool</b>	10	151105R
	12	151110R
	14	151120R
	15	151125R
	16	151130R
	18	151140R
	20	151145R
	22	151150R
	$\frac{3}{8}$ "	151155R
	$\frac{1}{2}$ "	151160R
	$\frac{5}{8}$ "	151165R
$\frac{3}{4}$ "	151170R	
$\frac{7}{8}$ "	151175R	
<b>REMS Twist/Hurrican drive unit with stabiliser</b>		151402R220
<b>Tool holder</b>		151200R
<b>Drill head</b>		151210RMM
<b>Dimpling pliers</b>		151230R
<b>Lubricant (tin)</b>		151240
<b>Case with inlay</b>		151618R

