

# REMS Pull L / M

Dry and wet extractor

Powerful, electric dry and wet extractor with automatic filter cleaning. For commercial use in trade and industry.

For extraction of dusts, dirt and liquids.

Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding.

Certified as extractor and dust extractor for extracting health hazardous dusts.

Ideal for extracting drilling sludge during core drilling.

## REMS Pull L

Dust class in accordance with EN 60335-2-69	L
Exposure limit/work place limit	> 1 mg/m <sup>3</sup>
Penetration level	≤ 1 %

## REMS Pull M

Dust class in accordance with EN 60335-2-69	M
Exposure limit/work place limit	> 0.1 mg/m <sup>3</sup>
Penetration level	≤ 0.1 %

**REMS Pull – for dry and wet suction.**  
**Constantly high suction performance**  
**by permanent automatic filter cleaning.**  
**Certified for extracting health hazardous dusts.**

### Universal use

Powerful, handy extractor for dry and wet suction. For extraction of dusts, dirt and liquids. Excellently suited for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified as an extractor and dust extractor for extracting health hazardous dusts of dust class L or M in accordance with EN 60335-2-69. For commercial use in trade and industry.

### Design

Compact, handy design. REMS Pull L/M only 12.7 kg. Light and manoeuvrable by rubber wheels and steerable castors, lockable by castor with brake. Large tank capacity 35 l, filling volume for liquids 19 l. On/off switch and switch for automatic filter cleaning with integrated green LED to display operation stand-by of the automatic filter cleaning. Adapter for connecting a power tool to the extractor, individually adaptable to the suction nozzle of the used power tool. Flexible suction hose 2.5 m, practical suction hose extension 2.5 m, ergonomically angled handle, 2 insertable, chrome-plated metal suction tubes 0.5 m for adapting the suction pipe length. Wide wet/dry surface attachment 300 mm with rubber-coated castors, optionally brush strips for extracting dusts and dirt or rubber lips for extracting liquids. Joint attachment for confined spaces. Large working radius by long 7.5 m connecting lead. Holders for connecting lead, suction hose, metal suction tubes and accessories integrated into the extractor. Practical handle for easy transport.

REMS Pull M is suitable and certified for the extraction of health hazardous dusts of dust class M in accordance with EN 60335-2-69, with electronic volume flow monitoring, selector switch for adapting the suction power to different suction hose diameters (21, 27, 35, 40, 50 mm) and stopper for the suction hose connection nozzle.

### Permanent automatic filter cleaning

REMS Pull L and REMS Pull M with innovative, patented, automatic filter cleaning, prevents clogging of the filter with dust, especially effective in fine dust applications. The flat folded filter is cleaned automatically every 15 s by targeted, powerful shots of air. The suction force remains constantly high during cleaning. Patented flat folded filter system.

### Drive

Robust, powerful bypass motor, 1,200 W, with high-power turbine. High suction power, continuously adjustable up to an air rate ≤ 74 l/s, for optimum adaptation to the suction surface and the extracted product.

### Automatic switch-off

Filling level limiting with automatic switch off on reaching the maximum liquid filling level when extracting electrically conductive liquids.

### Automatic power tool on/off

Appliance socket for power tools up to 2,200 W, with electronic automatic on/off integrated into the extractor. The extractor switches on/off automatically when the power tool is switched on/off. For convenient working.

### Anti-static system (REMS Pull M)

Static charge is dissipated to the earthed upper section of the extractor by electrically conductive metal suction pipes, electrically conductive handle E, electrically conductive suction hose E, electrically conductive suction hose extension E and electrically conductive suction hose connection nozzle.

### Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m<sup>3</sup>. Observe the national regulations.



Info



Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69.



Extraction of health hazardous dusts when chasing and cutting:  
REMS Pull M Set



Extraction of health hazardous dusts when dry drilling:  
REMS Pull M Set D

### Water extraction

PES flat folded filter required for extraction of water. Use wet filter bag or polythene bag if necessary. Wet filter bags separate the water from the sucked up solids when extracting dirty water. Polythene bags simplify disposal of the dirt and prevent dirt from collecting in the tank.

### Supply format

**REMS Pull Set.** Electric dry and wet extractor for commercial use. For extraction of dusts, dirt and liquids. Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69<sup>1)</sup>. Bypass motor 230 V, 50–60 Hz, 1,200 W. On/off switch and switch for automatic filter cleaning with integrated green LED. Suction power switch for continuous adjustment of the air rate  $\leq 74$  l/s. Filling level limiting with automatic switch-off. Automatic filter cleaning. Appliance socket for power tools up to 2,200 W, with electronic automatic on/off. Large tank capacity 35 l, filling volume for liquids 19 l. Mobile, 2 wheels, castor/castor with brake. Connecting cable 7.5 m. 1 paper filter bag, 1 flat folded paper filter. 2 metal suction pipes 0.5 m each, handle, suction hose 2.5 m, suction hose extension 2.5 m. Wet/dry surface attachment 300 mm with rollers, brush strips, rubber lips. Joint attachment. Suction hose/power tool adapter. Integrated holders for connecting cable, suction hose and accessories. In a box.

Description	Version	Art.-No.
<b>Pull L Set</b>	Dust class L. Exposure limit/work place limit $> 1$ mg/m <sup>3</sup> , penetration level $\leq 1$ %.	185500R220
<b>Pull L Set W</b>	REMS Pull L Set including water-resistant flat pleated filter PES and water extraction device. Ideal for extraction of drilling sludge when wet drilling with REMS drill stands.	185503R220
<b>Pull M Set</b>	Dust class M. Exposure limit/work place limit $> 0.1$ mg/m <sup>3</sup> , penetration level $\leq 0.1$ %. Electronic volume flow monitor with acoustic signal. Selector switch for suction hose diameter. Stopper for the suction hose connection nozzle. Anti-static system with electrically conductive metal suction pipes, handle, suction hose, suction hose extension, suction hose connection nozzle.	185501R220
<b>Pull M Set D</b>	REMS Pull M Set including suction rotor for dust extraction. Ideal for extracting health hazardous dusts when dry drilling with REMS Picus S1, Picus SR, Picus S3 etc.	185504R220



Extraction of drilling sludge when wet drilling with REMS drill stands:  
REMS Pull L Set W

Extraction of health hazardous dusts when chasing and cutting:  
REMS Pull L Set



REMS Pull L Set



Safety extractor of dust class L



Safety extractor of dust class M



REMS Pull M Set

### Accessories

Description	Art.-No.
<b>Paper filter bag (pack of 5)</b> , cellulose, 2-ply, for wet extraction, M-certified, for normal dirt, fine dusts	185510R05
<b>Felt filter bag (pack of 5)</b> , polyester felt, 3-ply, tear-proof, for wet and dry extraction, M-certified, for normal dirt, fine dusts, abrasive dusts, wet dirt	185511R05
<b>Wet filter bag (pack of 5)</b> , paper-polyester woven felt, tear-proof, for wet and dry extraction, for abrasive dusts, wet dirt, liquids	185512R05
<b>Polythene bag (pack of 10)</b> , for wet and dry extraction of non-health hazardous dusts, for normal dirt, fine dusts, abrasive dusts, wet dirt, liquids. Prevents soiling of the tank.	185513R10
<b>Flat, folded filter paper</b> , cellulose, nano-coated, 1 piece, for dry extraction, M-certified	185514R01
<b>Flat folded filter PES</b> , polyester, nano-coated, 1 piece, water-resistant, non-rotting, washable with water. For wet and dry extraction, M-certified	185515R01
<b>Adapter suction hose/power tool</b>	185527R



<sup>1)</sup> Observe the national regulations for the collection and disposal of health hazardous dusts.