

Universal, robust hand tool for cold bending up to 180°. Can be used anywhere. For trade and industry. For the building site and the workshop.

Hard, half-hard, soft copper tubes, also thin-wall \varnothing 10–22 mm \varnothing $\frac{3}{8}$ – $\frac{7}{8}$ "

Coated soft copper tubes, also thin-wall \varnothing 10–18 mm

Pipes of press fitting systems made of stainless steel, carbon steel (coated) \varnothing 12–18 mm
Carbon steel \varnothing 12–22 mm

Soft precision steel tubes \varnothing 10–20 mm

Electric conduit EN 50086 \varnothing 16–20 mm

Multi-layer composite tubes \varnothing 14–32 mm

REMS Sinus – wrinkle-free bending.

Universal for many tubes. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Only one type of bending and back formers for REMS Sinus and REMS Curvo.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Akku-Curvo 22V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, handy unit of bender drive and bending tools. Can be used anywhere, in parallel vice or free hand as double-hand-bender. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Robust design, drive unit in hardened steel for high stress. Simple and rapid changing of bending and back formers. Crossover, swan-neck and U-bends possible.

Bending formers and back formers

For different pipe sizes, materials and bending radii, see page 135.

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and for uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

Supply format


REMS Sinus Set. Hand tube bender \varnothing 10–32 mm, \varnothing $\frac{3}{8}$ – $\frac{7}{8}$ ", up to 180°. Hard, half-hard, soft copper tubes, also thin-wall \varnothing 10–22 mm, \varnothing $\frac{3}{8}$ – $\frac{7}{8}$ ", coated soft copper tubes, also thin-wall \varnothing 10–18 mm, pipes of the press fitting systems made of stainless steel, carbon steel (coated) \varnothing 12–18 mm, soft precision steel tubes \varnothing 10–22 mm, soft precision steel tubes, \varnothing 10–20 mm, electric conduit EN 50086, \varnothing 16–20 mm, multi-layer composite tubes \varnothing 14–32 mm and others. Drive unit, insert bolt. Bending formers and back formers. REMS bending spray. In sturdy steel case.

Description	Art.-No.
Set 15-18-22	154001
Set 14-16-18	154002
Set 12-15-18-22	154003
Set 10-12-14-16-18-22	154004
Basic-Pack (without bending and back formers and bending spray)	154010

REMS Sinus Set is delivered with bending formers and back formers of the smaller radius, see page 135.

Accessories

Description	Art.-No.
Bending and back formers see page 135.	
Insert bolt	582036
REMS Curvo drive unit	580000
REMS Sinus drive unit	154000
REMS bending spray, 400 ml	140120
Steel case with inlay	154160



German Quality Product



Info

